

Product Technical Data Sheet

3288T – Emulsion Cleaner

Summary

A cleaner designed to dissolve dried emulsion and thoroughly clean coating units and anilox chambers. Can be used on most waterbased materials including waterbased flexo inks. Will also remove paper dust and lint in one single step.

Properties

Flashpoint (°C)	>70C
Colour	Clear solution
Water Miscible	Yes
Density / Specific Gravity	0.95 +/- 0.020
Voc Content / % Volume	<40%
Odour	Characteristic
UN Number	N/A

Description of use

Can be used as a flush cleaner for the anilox coating unit, or used manually to clean waterbased deposits. Use pure for best results either manually using a lint free cloth or automatically (please consult press manufacturers guidelines for anilox chamber cleaning). Finish off with warm water after applying emulsion cleaner and allow to dry before restarting.

Storage, Shelf Life and Health and Safety

- Store in temperatures not exceeding 30°C and not falling below 5°C!
- Store on either pallets or racking in order to protect from cold floors.
- If left unopened and kept in the correct conditions this product has a recommended shelf life of 12 months.

Labeling: GHS07: Exclamation Mark
Usage: Will not give rise to any significant hazard provided reasonable standards of industrial practice are maintained.
Consult MSDS for further guidance.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

Total Graphic Supplies Ltd

Unit 7c Petre Court
Petre Road
Accrington
Lancashire
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk
Web: www.totalgraphics.co.uk