

Product Technical Data Sheet

5042TU – UV Wash

- Fast Evaporating UV Wash
- Suitable for use on automatic and manual cleaning systems
- Removes paper dust and fiber as well as waterbased deposits when mixed with water to ensure higher quality prints.
- Powerful cleaning with excellent ink solvency
- Not recommended for use on EPDM compound rubber.

Applications

Can be applied using either a manual cleaning system or an automatic cleaning program.

Properties

Flashpoint (°C)	>45C
Colour	Colourless
Water Miscible	Yes
Density / Specific Gravity	0.84
Voc Content / % Volume	100%
Odour	Aromatic
UN Number	1993

Machine / Systems

Has been formulated for use on the majority of automatic and manual cleaning systems. These include brush and cloth cleaning systems found on most Man Roland, Heidelberg, KBA, Komori and Mitsubishi presses.

Storage, Shelf Life and Health and Safety

- Store in temperatures not exceeding 30°C and not falling below 5°C!
- Store on either pallets or racking in order to protect from cold floors.
- If left unopened and kept in the correct conditions this product has a shelf life of 12 months.

Labeling:

GHS02: Flame
GHS07: Exclamation Mark
GHS08: Health Hazard
GHS09: Environmental

Usage:

Will not give rise to any significant hazard provided reasonable standards of industrial practice are maintained.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing development.

Total Graphic Supplies Ltd

Unit 7c Petre Court
Petre Road
Accrington
Lancashire
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk

Web: www.totalgraphics.co.uk