

Product Technical Data Sheet

5045TU – UV Meter Roll Cleaner

- Extremely fast evaporation
- Does not leave greasy residue
- Formulated to provide excellent cleaning and ink solvency on stubborn UV inks.
- A safer to use alternative to chlorinated solvents and MEK.

Applications

Designed for use most commonly as a manual wash to be used on the metering rollers, where quick evaporation is necessary to prevent contamination with other washes and/or the dampening water.

Properties

Flashpoint ([®] C)	~10C
Colour	Clear
Water Miscible	No
Density / Specific Gravity	0.825 +/- 0.020
Voc Content / % Volume	100%
Odour	Aromatic
UN Number	1993

Machine / Systems

Has been formulated for use on the majority of metering rollers. These include Man Roland, Heidelberg, KBA, Komori and Mitsubishi presses.

Testing is always recommended to ensure suitability.

Storage, Shelf Life and Health and Safety

- Wear Appropriate safety clothing when handling consult MSDS for details.
- If left unopened and kept in the correct conditions this product has a shelf life of 12 months.
- Avoid sources of ignition

Labeling:	GHS02: Flame
	GHS07: Exclamation Mark
	GHS08: Health Hazard
	GHS09: Environmental
Usage:	Will not give rise to any significant
	hazard provided reasonable standards
	of industrial practice are maintained.

<u>Note</u>

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

Total Graphic Supplies Ltd

Unit 7c Petre Court Petre Road Accrington Lancashire BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk Web: www.totalgraphics.co.uk