

Product Technical Data Sheet

C610 – RAPID WASH

- Extremely fast evaporation leaving non-greasy residue.
- Formulated to provide excellent cleaning and ink solvency
- A safer to use alternative to chlorinated solvents and MEK.

Applications

C610 is designed for use most commonly as a manual wash to be used on the dampening metering rollers, to quickly and efficiently removal ink contaminants whilst promoting the hydrophilic nature of the rollers.

Properties

Flashpoint (°C)	-25C
Colour	Clear
Water Miscible	No
Density / Specific Gravity	0.700 +/- 0.020
Voc Content / % Volume	100%
Odour	Medium
UN Number	1268

Machine / Systems

C610 has been formulated for use on the majority of metering rollers. These include Man Roland, Heidelberg, KBA, Komori and Mitsubishi presses.

Testing is always recommended to ensure suitability.

Storage, Shelf Life and Health and Safety

- Store in temperatures not exceeding 30°C and not falling below 5°C!
- Store on either pallets or racking in order to protect from cold floors.
- If left unopened and kept in the correct conditions this product has a shelf life of 12 months.

Labeling: GHS02: Flame
GHS08: Health Hazard
GHS09: Environmental

Usage: Will not give rise to any significant hazard provided reasonable standards of industrial practice are maintained.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

Total Graphic Supplies Ltd

Unit 7c Petre Court
Petre Road
Accrington
Lancashire
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk
Web: www.totalgraphics.co.uk