

# Demi Gloss Coated Paper

A 220gsm demi gloss solvent coated paper for high quality posters.

TECHNICAL SPECIFICATION			AVAILABLE SIZES		
	Value	T Method			
Weight (gsm)	220	ISO 536	1372mm	(54")	X 50m
Caliper (µm)	200	ISO 534	1600mm	(63")	X 50m
Opacity (%)	98.7	D65			
Tear Strength (mN)	MD = 850	ISO 1974			
	CD = 950				
Stiffness (mNm)	MD = 4.6	ISO DP 5629			
	CD = 2.8				

## APPLICATIONS AND CHARACTERISTICS

- "Demi Gloss" surface finish.
- Highest quality colour reproduction.
- Crisp sharp image reproduction
- Excellent handability
- The special coating enables less ink to be used.

## PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

MANUFACTURER	MODEL	INKS
--------------	-------	------

All of our products undergo thorough testing on all leading printers and with all major manufactured inks. But to guarantee that you get the best possible results every time from our products and printers inks, it is advisable to consult your representative.

## Fire Hazard

This media exhibits burning rates and hazards similar to other pure PVC or cellulose based products of equivalent thickness. Considerable heating above ambient conditions is required before ignition and combustion can occur. The products of combustion depend on the burning conditions and are likely to include carbon monoxide, oxides of nitrogen. In the event of fire, fire fighters should wear self contained breathing apparatus and protective clothing. Extinguish with water spray, carbon dioxide, dry chemical

## STORAGE AND TRANSPORT

The ideal storage conditions for this product are 33-65% relative humidity with temperatures of 10-25 °C. We recommend that you always keep this product in its original packaging (in both the plastic bag and cardboard box)