

WATER CONDITIONER



Rehardener for RO water or natural soft water

KEY CHARACTERISTICS

Dosage: up to 0,5 % %

Concentrate

For sheetfed, heatset and coldset application

pH value: 7,1

 Adjusts process water to a definite water hardness

PACKAGING

1000L IBC 600L IBC 200L plastic drum 25L jerrycan 10L jerrycan

FEATURES AND BENEFITS

Universal in use

Compatible with all fount concentrates

Consistent water quality

- Water quality will be kept stable
- Stable ink-water balance
- Constant print quality
- Constant pH and conductivity of the fountain solution

INSTRUCTIONS FOR USE

With addition of 0,5 % rehardner to demineralized or reverse osmosis water, the water hardness will be increased by 10 °dH. Will be water used with higher or lower total hardness the water can be adjusted to the required circumstances.

TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 $\mathbb C$ or below -1 0 $\mathbb C$.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

Version 1.0, state 2/02/2012 - Our Products are intended for sale to professional users. The information herein is general information designed to assist customers in determining the suitability of our products for their applications. All recommendations are made without guarantee, since the application and conditions of use are beyond our control. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In no event shall Sun Chemical be liable for damages of any nature arising out of the use or reliance upon this information. Modifications of the product for reasons of improvements might be made without further notice.