

#### **Ideal for new business challenges**

The popular Kodak Trendsetter 800 Platesetter is designed to meet the new challenges of today's business environment. Based on the same trusted technology that printers have depended on for over 14 years, the Trendsetter Platesetter has a small footprint and a powerful thermal imaging head for maximum productivity with Kodak Sonora XP Process Free Plates. The fast throughput, reliability, and stable, high-quality thermal imaging of the Trendsetter 800 Platesetter can help you exceed your customers' expectations, efficiently and affordably. To succeed in today's changing market, you need products and technologies that can adapt, and Kodak keeps investing in the Trendsetter Platesetter to help you excel, now and in the future.

### Reliable, flexible plate making

In order to maximize the profitability of your business, you need to have a CTP system that will make quality plates day in and day out. Downtime, plate remakes, and poor imaging quality will quickly wipe out any cost benefits from low-cost platesetters or consumables. The **Trendsetter** 800 Platesetter not only gives you the stability and reliability you need to optimize your prepress operation, you can choose from several automation and speed options, so your investment can match your unique business needs and be easily upgraded as business grows.

#### **Accurate and stable imaging**

Kodak squarespot Imaging Technology, standard in every Trendsetter 800 Platesetter, delivers dependable accuracy regardless of plate emulsion sensitivity, processor variation, and laser power. Thermal compensation technology enables accurate and consistent imaging from plate to plate and machine to machine. This stability not only enables you to reduce costs through fewer remakes and less time adjusting for variables, it allows you to differentiate and grow your business through high-resolution printing. The Kodak Trendsetter 800 Quantum Platesetter, combined with optional 10-micron Kodak Staccato Screening and Kodak Digital Plates, delivers stunning photorealistic results that you have to see to believe.

### Increase your sustainability

With the **Trendsetter** 800 Platesetter, maximizing quality and productivity can also help you minimize environmental impact. The small footprint reduces shipping waste and costs, as well as space requirements. Choosing **Kodak Sonora** XP Process Free Plates will further reduce your environmental impact by completely eliminating your plate processor and chemistry and reducing maintenance costs and labor, without compromising on quality or productivity.

# Kodak Trendsetter 800 Platesetter

General specifications			
Technology	830 nm thermal imaging platesetter, semi-automatic, external drum		
Load/unload systems	Standard: Semi-automatic plate loading and unloading		
	Auto Unload: Semi-automatic plate loading and automatic unloading to plate processor or stacker; automatic plate rotation		
	Autoloader: Automated plate loading and unloading of up to 40 plates without slip sheets (0.3 mm)		
Performance specifications			
Throughput at 2400 dpi <sup>1,2</sup>	Standard and Auto Unload:	Autoloader:	
for plate size 1030 x 838 mm	S speed = 15 plates per hour	S speed = 16 plates per hour	
(40.5 x 33 in)	F speed = 22 plates per hour	F speed = 24 plates per hour	
	V speed = 30 plates per hour	V speed = 34 plates per hour	
	X speed = 34 plates per hour	X speed = 42 plates per hour	
Repeatability <sup>3</sup>	± 5 microns (± 0.2 mil) between two consecutive exposures on the same plate left on the drum		
Accuracy <sup>3</sup>	$\pm$ 20 microns ( $\pm$ 0.8 mil) between two plates imaged by different <b>Trendsetter</b> Platesetters		
Registration <sup>3</sup>	± 25 microns (± 1.0 mil) between image and plate edge		
Workflow connectivity	Kodak Prinergy Evo Workflow, Kodak Prinergy Workflow, and connection to third-party workflow systems		
Imaging specifications			
Resolution	2400 dpi (94.4 dpmm) or 1200 dpi (47.2 dpmm)		
Screening	Trendsetter 800 Platesetter: • 250 lpi max line screen • Optional 25-micron Kodak Staccato Screening	Trendsetter 800 Quantum Platesetter:  • 450 lpi max line screen  • Optional: 20- or 10-micron Kodak Staccato Screening	
Maximum plate size: around drum x along drum <sup>4</sup>	<b>Standard:</b> 838 x 1,143 mm (33 x 45 in)	<b>Auto Unload:</b> 838 x 1,118 mm (33 x 44 in)	<b>Autoloader:</b> 838 x 1,118 mm (33 x 44 in)
Minimum plate size:	267 x 215 mm (10.5 x 8.5 in)	383 x 270 mm (15.1 x 10.6 in)	383 x 270 mm (15.1 x 10.6 in)
around drum x along drum <sup>4</sup>		Manual unload:	Manual load and unload:
		267 x 215 mm (10.5 x 8.5 in)	305 x 215 mm (12 x 8.5 in)
Maximum image area: around drum x along drum	827.9 x 1,143 mm (32.6 x 45 in)	827.9 x 1,118 mm (32.6 x 44 in)	827.9 x 1,118 mm (32.6 x 44 in)
Physical characteristics			
Size (H x W x D)	Standard:	Auto Unload:	Autoloader:
	160 x 200 x 120 cm	210 x 200 x 180 cm	210 x 200 x 180 cm
	(63 x 79 x 48 in)	(83 x 79 x 71 in)	(83 x 79 x 71 in)

## Weight 650 kg (1,433 lbs) 744 kg (1,640 lbs) 1 Imaging speed and throughput is dependent on media sensitivity. All values are for media sensitivity of 120mJ/cm²

- 2 Tested with Kodak Workflow Solutions. For additional information about the test conditions, please consult your Kodak representative.
- 3 For devices that are not **Quantum** models, these specifications pertain to performance at largest plate size, over constant temperature. For **Quantum** devices, specifications pertain to performance at largest plate size, over full temperature range.

 $The \ platesetter \ is \ a \ Class \ 1 \ Laser \ Product \ and \ fully \ complies \ with \ EN 60825-1 \ and \ US \ Federal \ Regulations \ 21 \ CFR \ 1040.10 - CDRH.$ 

#### To learn more about solutions from Kodak:

Visit graphics.kodak.com

Produced using Kodak Technology.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA

©Kodak, 2012. Kodak, Prinergy, Prinergy Evo, Quantum, Staccato, SQUARESPOt, Sonora and Trendsetter are trademarks of Kodak.

Subject to technical change without notice.



Height is to top of unload table in

raised position.

750 kg (1,653 lbs)

<sup>4</sup> Standard plate gauge is 0.14 to 0.3 mm (0.0055 to 0.012 in). Option available for plate gauge of 0.14 to 0.4 mm (0.0055 to 0.016 in) For plate gauges 0.14 to 0.2 mm (0.0055 to 0.08 in) there may be some differences in min and max. plate sizes. For more information, please consult your Kodak representative.